


even

DESIGN INC.

DETERMINING RING SIZE

Please carefully read all instructions as the measurements may not be accurate if not done properly..


CONFIRM PRINTED PAPER SIZE



1. PRIOR TO PRINTING, ENSURE THAT PAGE SCALING IS SET TO "NONE" ON YOUR PRINT DIALOGUE BOX.
2. MEASURE THE BAR BELOW TO ENSURE IT IS EXACTLY 2 INCHES LONG.
3. IF MEASUREMENT IS NOT ACCURATE, CHECK THAT YOU ARE PRINTING THE PAGE AT FULL SIZE AND REPRINT BEFORE CONTINUING.

METHOD A - MEASURE FINGER WITH PAPER SIZER.

1. Carefully cut along the outline of the sizer as well as the small slit at the left end of the sizer.
2. Wrap the sizer around the intended finger* with the numbers facing out.
3. Slide the pointed end of the sizer through the slit.
4. Move the sizer to the largest part of the finger, this may be the knuckle.
5. **Pull tightly. The sizer must fit snugly to produce an accurate size.**
6. The number that lines up at the slit represents the ring size for that finger.



NOTES FOR ACCURATE MEASURING

- Avoid measuring cold fingers as this is when fingers are at their smallest.
- Measure your finger when it is at it's largest, at the end of the day.

METHOD B- MEASURE CURRENT RING

1. Select a ring that properly fits the intended finger*
2. Place the ring over the circles below, matching the inside size of the ring to the circle nearest in size.
3. If the ring falls between two sizes, order the larger size.



*the "ring finger" is located between the little finger and middle finger.
Engagement and wedding rings are worn traditionally on the ringfinger on the left hand.

For assistance please call 1.604.732.7248 or email: judi@evendesigninc.com
<http://evendesigninc.com>